

System	
OS	Android 10
CPU	MT6765, octa-core (4 cores @ 2.3 GHz + 4 cores @ 1.8 GHz)
RAM	4GB
Storage	64GB
External Storage	Micro SD, hot-swappable, up to 128GB
Physical	
Size (L x W x H)	225mm x 80mm x 17.0mm (8.86 in x 3.15 in x 0.67 in)
Weight	400g (0.88lb)
Environment	Operating: -30°C to +60°C (-22°F to +140°F) Storage: -40°C to +70°C (-40°F to +185°F)
Ingress protection	IP67
Drop	Survive a 2m (6.5 ft) drop onto concrete
Display	5.5" HD+ capacitive multi-touch screen, 1440 x 720 pixels resolution, typical brightness 600 cd/m² Supports stylus, gloves, and wet hand operation.
Keypad	Alphanumeric keyboard
Camera	8 MP rear camera with auto-focus flashlight
Sensor	G-sensor, proximity sensor, light sensor, e-compass, gyroscope
Electrical	
Battery	Built-in, rechargeable Li-ion battery, 3.8V
Battery capacity	8000mAh
Operating time ⁽¹⁾	14h
Charging time	4h (typical)

TECHNICAL SPECIFICATIONS

Communication	
Wireless connection	NFC for device touch pairing, 13.56MHz
SIM Card type	Nano-SIM card
Network	Integrated 4G modem: LTE FDD: B1/B2/B3/B4/B5/B7/B8/B12/B17/B20/B28AB LTE TDD: B34/B38/B39/B40/B41 Integrated 3G modem: WCDMA: B1/B2/B4/B5/B8 CDMA EVDO: BC0
Wi-Fi	IEEE 802.11 a/b/g/n/ac/r, 2.4G/5G dual frequency
Bluetooth	BT5.0 + BLE
Ports	1 x USB Type-C port



*All specifications are subject to change without notice.
(1) Battery life is subject to operating temperature and usage conditions.

Shanghai EFIX Geomatics Co., Ltd.

Room 1137, D, 11/F, Building 1, No. 158 Shuanglian Road, Qingpu District, Shanghai
Sales@efix-geo.com
www.efix-geo.com

© EFIX Geomatics Co., Ltd. All rights reserved. All rights reserved. The EFIX logo are trademark of EFIX Geomatics Co., Ltd.
All other trademarks are the property of their respective owners. Revision October 2024.



Boost Stakeout Efficiency By 50%



FC2

HANDHELD CONTROLLER